

# F4

## Form 4

BEAMS



### FEATURES

- Rectilinear shape
- Direct/Indirect; direct only or indirect only distribution
- Internal extruded aluminum chassis and outer steel housing provides excellent strength and rigidity
- Die-cast aluminum end caps provide stylish, subtle fixture ends
- Available with lenses or parabolic louvers
- Wide assortment of lighting distributions
- UL listed 1598. Damp Label available on most models

### ORDERING INFORMATION

<b>F4</b>			<b>T8</b>						
MODEL	LAMP PROFILE & DISTRIBUTION	LAMP TYPE	SUSPENSION LENGTH	VOLTAGE	FINISH	OPTIONS			
F4 Form 4	<b>1U</b> 1-Lamp Uplight <b>1AU</b> 1-Lamp Asymmetric Uplight <b>1UD</b> 1-Lamp Uplight & Downlight <b>1D</b> 1-Lamp Downlight <b>1AD</b> 1-Lamp Asymmetric Downlight <b>2U</b> 2-Lamp Uplight <b>2UD</b> 2-Lamp Uplight & Downlight <b>2D</b> 2-Lamp Downlight	T8 T8	<b>48</b> 48" <b>96</b> 96" Not applicable for surface or wall mount. Other lengths available on request.	<b>U</b> 120V-277V <b>120</b> 120V <b>277</b> 277V <b>347</b> 347V	<b>MW</b> Matte White (Std.) <b>ZT</b> ZET Metallic Silver See page 185 for other color selections.	<b>DC</b> Dust Cover <b>LR</b> Left/Right Switching (2-Lamp only) <b>EL</b> One Emergency Battery Pack <sup>2,3</sup> <b>EMC</b> One Emergency Circuit <sup>3,4</sup> <b>NL</b> Night Light Circuit <sup>3,4</sup> <b>GLR</b> Fast Blow Fuse <b>GMF</b> Slow Blow Fuse <b>TBAR</b> T-Bar Mounting <b>CSA</b> UL listed or CSA certified for Canada <b>DL</b> Damp Label (Available on most models)			
ROW LENGTH			MOUNTING METHOD	SHIELDING	BALLAST				
<b>4</b> 4' Single <b>8</b> 8' Single — Indicate row length over 8' in 4' increments <b>Note:</b> Rows over 8' will be configured by Alera. Example: 16' will be (2) 8'. Alternate configurations: contact factory.			<b>CM</b> Adjustable Aircraft Cable <b>PM</b> Pendant Mount <b>SM</b> Surface Mount (Direct Only) <b>WM</b> Wall Mount, Symmetric Dist. <b>WMW</b> Wall Mount, Wall Wash <sup>1</sup> <b>WMR</b> Wall Mount, Room Wash <sup>1</sup>	<b>LD</b> Low Iridescent Semi-Specular Louver <b>LS</b> Low Iridescent Specular Louver <b>A12</b> Pattern 12 Acrylic Lens <b>A19</b> Pattern 19 Acrylic Lens <b>CA</b> Clear Acrylic Lens (No pattern) <b>OA</b> Opal Acrylic Lens <b>WCB</b> White Cross Baffle <b>NA</b> No Shielding	<b>E</b> Electronic, Instant Start (Std. for T8) <b>EP</b> Electronic, Programmed Start <b>ED</b> Electronic, Dimming (Must Specify) <b>ESD</b> Electronic, Step Dimming Unless specified, Alera will use fewest ballasts possible.				
			See pages 180-181 for other hanging methods.						

<sup>1</sup> For use with asymmetric distributions.

<sup>2</sup> Specify voltage. For additional, specify quantity before nomenclature (Example: 2EL120).

<sup>3</sup> Not available with all configurations; some limitations apply. Contact factory for details.

<sup>4</sup> One extra feed drop per row with through wiring. (Standard is one 4ft lamp per circuit.)

### CROSS SECTIONS

